




Diversified Architectural Lighting Inc.

939 Selkirk Ave., Pointe-Claire, Qc, Canada H9R 4S4
 Tel : 514.693.2117 Fax : 514.693.2177

Project :	Agent :
Type :	Approved by :
Cat No :	Date :



WMS mounting style

CT3-WMD/WMS contour series

Luminaire:

Ballast housing is fabricated of one piece heavy-duty cast aluminum. Aluminum spacers fasten the ballast housing to the spun aluminum shade. Three decorative aluminum rings are placed along the spacers to allow minimal uplight. Borosilicate glass refractor is fastened directly to the ballast housing and is enclosed with a polycarbonate globe.

Mounting:

The luminaire is supported by twin arms welded to a rigid aluminium wall plate that is attached to the wall around the junction box.

Optics:

Type III or type V distribution available.

Protection:

The luminaire is completely protected from water and dust. A threaded spun aluminum holder overlaps the tempered glass refractor. Cast aluminum ballast housing is sealed with a cast aluminum plate which is gasketed.

Maintenance:

Quick and easy lamp maintenance through removing globes

Electrical:

Standard metal halide and high-pressure sodium luminaires are supplied with core and coil CSA / UL listed ballasts. All ballasts are guaranteed for at least 2 years directly from the ballast manufacturer. Components are horizontally opposed for thermal reduction. All components are mounted on a single plate for easy maintenance.

Pulse start metal halide luminaires are supplied with standard uniform pulse start systems suitable for vertical lamp mounting. All components are mounted on a single plate for easy maintenance. Pulse start systems are guaranteed directly from the manufacturer for a period of 5 years.

Compact fluorescent: All compact fluorescent luminaires are supplied with electronic ballasts. Consult factory for dimming ballast to match controls and ballasts. In the case where the luminaire uses multiple ballasts, the ballasts are mounted on a single plate and can be individually removed.

Model #	Mounting	Ring	HID(wattage)	CFL(wattage)	Voltage**	Color	Options
CT3	WMD Wall mounted down (straight arm) WMS Wall mounted with shepherd's hook (as shown)	AL- aluminum BA- blue acrylic CA- clear acrylic	50MH-PS* 50HPS	26DTT	TT MT tri-tap multi-tap 120 120 277 208 347 240 277	CC-Custom Color *** BLK-Black WHT-White SIL-Silver BRZ-Bronze	QRT-Quartz re-strike F-Fusing PC-Photocell
			70MH-PS* 70HPS				
			100MH-PS* 100HPS				
			175MH-PS* 150HPS				
			250MH-PS* 250HPS				
			42TRT				

*PS stands for pulse start
 ** Not all voltages are available for all lamp types
 ***Either supplying factory with a color chip or a RAL number can specify custom color. (Some custom colors will be subject to a small lot setup charge)

Ordering example:
 CT3-WMD-AL-100MH-PS-120-BRZ
 This would order: Contour, wall mounted down with aluminum rings, 100W MH-PS, 120V, painted bronze.

contour