





Diversified Architectural Lighting Inc.

939 Selkirk Ave., Pointe-Claire, Qc, Canada H9R 4S4
 Tel : 514.693.2117 Fax : 514.693.2177

Project :	Agent :
Type :	Approved by :
Cat No :	Date :



DK8-WMU / DK8-WMD dramatek series - Wall mount -

Luminaire

Cast aluminum ballast housing is attached to spun aluminum cylindrical housing. Spun aluminum reflector is fastened to spun aluminum screw base refractor holder. Extruded aluminum arm is welded to cast aluminum wall mount canopy. All lampholders are medium base rated 4KV c/w copper nickel plated screwshell.

Optics

Anodized aluminum reflector offers optimal light distribution. Black multi-step baffle is installed at the bottom of the cylinder to ease glare. Reflector can be offered with a tilt to accentuate wall illumination. Optics can also be modified with a prismatic lens, prismatic refractor or frosted lens. May be used with ED-17 or PAR 38 HID lamps.

Protection/Enclosure

These units are certified for indoor or outdoor use. Typically the luminaire is supplied with a black multi step baffle and a prismatic refractor. The cylinder can also be enclosed with a flat glass which can be prismatic, frosted or clear. The bottom can also be left open for interior use.

Electrical:

Standard metal halide and high-pressure sodium luminaires are supplied with core and coil CSA/UL listed ballasts. All ballasts are guaranteed for at least 2 years directly from the ballast manufacturer. Components are horizontally opposed for thermal reduction. All components are mounted on a single plate for easy maintenance.

Pulse start metal halide luminaires are supplied with standard uniform pulse start systems suitable for universal lamp mounting. All components are mounted on a single plate for easy maintenance. Pulse start systems are guaranteed directly from the manufacturer for a period of 5 years.

Compact fluorescent: All compact fluorescent luminaires are supplied with electronic ballasts. Consult factory for dimming ballast to match controls and ballasts. Where the luminaire uses multiple ballasts, the ballasts are mounted on a single plate and can be individually removed.

Model #	Mounting	HID(wattage)		CFL(wattage)	Voltage**		Color	Options
DK8 (ribbed)	WMD Wall mounted down	50MH-PS*	50HPS	18DTT	TT	MT	CC-Custom Color ***	QRT-Quartz re-strike
		70MH-PS*	70HPS	26DTT	tri-tap	multi-tap	BLK-Black	F-Fusing
DK8SH (Smooth housing)	WMU Wall mounted up	100MH-PS*	100HPS	32TRT	120	120	WHT-White	FG-Flat glass
		150MH-PS*	150HPS	42TRT	277	208	SIL-Silver	PL-Prismatic flat glass
		175MH-PS*			347	240	BRZ-Bronze	FL-Frosted lens
						277		PC-Photocell
								TR-Tilted reflector

*PS stands for pulse start
 ** Not all voltages are available for all lamp types
 ***Either supplying factory with a color chip or a RAL number can specify custom color. (Some custom colors will be subject to a small lot setup charge)

Ordering example:
 DK8-WMD-100MH-PS-120-BRZ
 This would order: Dramatek wall mounted down, 100W MH-PS, 120V painted bronze.